

SAFETY DATA SHEET - CARBON DIOXIDE Version 2.1 17/10/12

1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY

Product Identifier/Name:	Carbon Dioxide	
Chemical Formula:	CO2	
Uses of the substance: Restrictions on use:	Drinks dispense & Industrial. no data available	
Company Identification:	Gas Link Wales Ltd	
Emergency Telephone No:	01443 222092	
Email:	james@gaslinkwales.co.uk	
2. HAZARDS IDENTIFICATION:		
Classification according to regulation 1272/2008 (CL Compressed Gas H280: Contains gas under pressure; n	•	
Label elements according to regulation 1272/2008 (CLP) Hazard pictograms/symbols		
Signal Word:	Warning	
Hazard Statements:	H280: Contains gas under pressure. May explode if heated.	
Precautionary Statements:	P403: Store in well-ventilated area.	
Classification (Directive)		
Not a hazardous substance or preparation according to No EC labelling required	EC-directives 67/548EEC or 1999/45/EC	
Other Hazards Can cause rapid suffocation. Compressed liquefied gas. Avoid breathing gas. Direct contact with liquid can cause frostbite.		

Self contained breathing apparatus (SCBA) may be required



SAFETY DATA SHEET - CARBON DIOXIDE Version 2.1 17/10/12

3. COMPOSITION/ INFORMATION ON INGREDIENTS

CAS Number: EEC Number:	124-38-9 204-69-6 (from EINECS)
Concentration:	100%
4. FIRST AID MEASURES	
Description of first aid measures:	
General advice:	Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing has stopped
Eye & Skin Contact:	Adverse effects not expected
Ingestion:	Ingestion is not considered a potential route of exposure.
Inhalation:	Move victim to fresh air. If breathing has stopped, apply artificial respiration. In case of shortness of breath, give oxygen. Keep victim warm and rested. Call Doctor.
Symptoms of asphyxiation:	Shivering, sweating, blurred vision, headache, shortness of breath, rapid breathing, loss of coordination and mobility and nausea.
5. FIRE FIGHTING MEASURES	
Suitable Extinguishing Media:	All known extinguishing media can be used.
Specific Hazards:	Exposure to fire may cause containers to rupture/ explode. Non-flammable.
Advice for firefighters:	If safe to do so, stop flow of product. Move container away or cool with water from a protected position. In confined spaces use

self-contained breathing apparatus.



Version 2.1 17/10/12

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Monitor CO2 level. Wear self-contained breathing apparatus when

entering area unless atmosphere is proved to be safe. Monitor oxygen

levels. Evacuate area. Ensure adequate air ventilation.

Environmental Precautions: Should not be released into the environment. Prevent further leakage

if safe to do so. Prevent from entering sewers, basements and work

pits or any place where its accumulation could be dangerous.

Clean Up Methods: Ventilate area.

Additional advice: Increase ventilation to the release area and monitor concentrations. If

leak is from cylinder or cylinder valve, call the Gas-Link Wales emergency number. If leak is in the users system, close the cylinder valve, safely vent the pressure, and safely vent the pressure before

attempting repairs.

7. HANDLING AND STORAGE

Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C (122°F). Only experienced and properly trained persons should handle compressed gases/cryogenic liquids. Before using the product determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When in doubt as to the correct handling procedure for a particular gas, contact the supplier.

Do not remove or deface content identifying labels. When moving cylinders, even for short distances, use cylinder trolley or hand truck designed to transport cylinders. Leave valve protection guards in place. Secure cylinders against either a wall or bench or place in a cylinders stand. Before connecting cylinder, check the complete gas system for suitability, in particular check pressure rating and material compatibility. Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close cylinder valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be immediately reported to the supplier.

Do not subject cylinders to abnormal mechanical shocks which may cause damage to their valve or safety devices. Never attempt to lift a cylinder by its valve protection cap or guard. Do not use cylinders as rollers or supports or for any purpose other than to contain the gas as supplied. Never strike an arc on a compressed gas cylinder or make a cylinder part of an electrical circuit. Do not smoke while handling product or cylinders. Never recompress a gas or a gas mixture. Never attempt to transfer gases from one cylinder to another. Always use backflow protection devices in piping. Never use direct flame or electrical heating devices to raise the pressure of a cylinder. Prolonged periods of cold temperature below -30° C ($20F^{\circ}$) should be avoided. Suck back of water into container must be prevented. Purge air from system before introducing gas. Do not allow back feed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature.



Version 2.1 17/10/12

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Control parameters:

Exposure limit(s)

Carbon dioxide Time weighted average (TWA): EH40

WEL 5,000ppm 9,150 mg/m3

Carbon dioxide Short Term Exposure limit STEL): EH40 WEL

15,000ppm 27,400 mg/m3

Carbon dioxide Time weighted average (TWA): EU ELV

5,000ppm 9,000 mg/m3

Exposure Controls: Provide Natural or mechanical ventilation to prevent accumulation above

exposure limits. Systems should be regularly checked for leakage. Oxygen

detectors should be used

Personal protective equipment

Respiratory protection: Self-contained breathing apparatus (SCBA) or positive pressure airline with

mask are to be used in oxygen deficient atmosphere.

Air purifying respirators will not provide protection. Users of breathing

apparatus must be trained.

Hand protection: Sturdy work gloves are recommended for handling cylinders. The

breakthrough time of the selected gloves must be greater than the intended

use period.

Eye protection: Safety glasses recommended when handling cylinders.

Skin & body protection: Safety footwear is recommended when handling cylinders.

Special instructions for

protection and hygiene: Ensure adequate ventilation, especially in confined areas.



Version 2.1 17/10/12

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/ Colour: Liquefied gas, Colourless gas.
Odour: No odour warning properties

Odour threshold:

pH:

Melting point range:

Boiling point range:

Flash point

Evaporation Rate

No data available

Not applicable

Not applicable.

Not applicable.

Upper/Lower

Flammability (solid/gas)

Explosion/flammability limit: No data available Vapour pressure: 57.3 bar @ 20 °C

Water solubility: 2.000g/l
Relative vapour density: 1.519 (air = 1)
Relative density: 0.82 (water = 1)

Partition coefficient

(n-octanol/water)
Auto ignition temperature:
Decomposition temperature:
Viscosity:
Explosive properties:
Oxidizing properties:
Molecular weight:
Not applicable
No data available
No data available
No data available
44.01g/mol

Density: 0.0018 g/cm³ (0.112lb/ft³) at 21°C (70°F) Note: (as vapour)

Specific volume: 0.5456 m³/kg at 21 °C

10. STABILITY AND REACTIVITY

Reactivity: refer to possibility of hazardous reactions and/or incompatible

materials sections.

No data available

Chemical Stability: Stable under normal conditions.

Possibility of

hazardous reactions: No data available. Conditions to avoid: No data available.

Hazardous decomposition

products: No data available.



Version 2.1 17/10/12

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects.

Effects on eyes: Contact with liquid may cause cold burns/frostbite

Effects on skin: Contact with liquid may cause cold burns/frostbite.

Inhalation effects: Concentrations of 10% CO2 or more can produce unconsciousness

or death. Unlike simple asphyxiants, carbon dioxide has the ability to

cause death even when normal oxygen levels (20-21%) are maintained. Carbon dioxide is physiologically active, affecting circulation and breathing. At concentrations between 2 and 10%, carbon dioxide can cause nausea, dizziness headache, mental confusion, increased blood pressure and respiratory rate. In high concentrations may cause asphyxiation. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without

warning and so rapidly that victim may be unable to protect

themselves.

Ingestion effects: Ingestion is not considered a potential route of exposure.

Symptoms: Exposure to oxygen deficient atmosphere may cause the following

symptoms; dizziness, Salivation, Nausea, Vomiting, Loss of

mobility/consciousness.

Acute oral toxicity: No data available on the product itself.

Inhalation: Unlike simple asphyxiants, carbon dioxide has the ability to cause

death even when normal oxygen levels (20-21%) are maintained. 5% Co2 has been found to act synergistically to increase the toxicity of certain other gases (CO2 NO2). CO2 has been shown to enhance the production of carboxy- or met-haemoglobin by these gases possibly due to carbon dioxide's stimulatory effects on the respiratory

and circulatory systems.

Acute dermal Toxicity: No data available on the product itself.

Skin corrosion/irritation:

Serious eye damage

No data available

/eye irritation:

No data available
Sensitisation:

No data available.

Chronic toxicity or effects from long-term exposure.

Carcinogenicity: No data available

Reproductive toxicity: No data available on the product itself. Gem cell mutagenicity: No data available on the product itself.

Specific target organ systemic

toxicity(single exposure):

No data available.

Specific target organ systemic

toxicity(repeated exposure): No data available on the product itself.

Aspiration hazard: No data available.



Version 2.1 17/10/12

12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: No data available on the product itself.

Toxicity to fish -Components:

Carbon dioxide: LC50 (1h): 240 mg/l Species: Rainbow trout. (Oncorhynchus mykiss)
Carbon dioxide LC50 (96h): 35mg/l Species: Rainbow trout (Oncorhynchus mykiss)

Toxicity to other organisms:

Persistence and degradability:
Bio accumulative potential:

Mobility in soil:

No data available on the product itself.

No data available on the product itself.

No data available on the product itself.

Results of PBT and

vPvB assessment: If applicable refer to extended version of SDS for further information

on CSA.

Other adverse effects: When discharged in large quantities may contribute to greenhouse

effect

13. DISPOSAL CONSIDERATIONS

Waste treatment methods: Contact Gas Link Wales if guidance is required.

Return unused product in original cylinder to supplier.

Contaminated packaging: Return cylinder to supplier.

14. TRANSPORT INFORMATION

ADR

UN ID No. : UN1013
Proper Shipping Name . Carbon Dioxide

Class/ Division: 2.2
Tunnel code: (C/E)
Hazard Identification No.: 2.0
Label(s): 2.2

IATA

UN ID No. : UN1013

Proper Shipping Name . Carbon Dioxide

Class/ Division: 2.2 Label(s): 2.2

IMDG

UN ID No.: UN1013

Proper Shipping Name . Carbon Dioxide

Class/ Division: 2.2 Label(s): 2.2

RID

UN ID No.: UN1013

Proper Shipping Name . Carbon Dioxide

Class/ Division: 2.2 Label(s): 2.2



Version 2.1 17/10/12

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or emergency.

Before transporting product containers check that they are firmly secured and ensure:

- •
- Cylinder valve outlet is closed and not leaking.
- Valve outlet cap, nut or plug (where provided) is correctly fitted.
- Valve protection device (where provided) is correctly fitted).
- Adequate ventilation.
- Compliance with applicable regulations

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture,

Country	Regulatory List	Notification
USA	TSCA	Included on Inventory
EU	EINECS	Included on Inventory

WGK Identification Number: Not water endangering.

Chemical Safety Assessment

This product does not meet the minimum volume threshold. CSA has not yet been completed.

16. OTHER INFORMATION

Ensure all national/ local regulations are observed.

Hazard statements: H280 Contains gas under pressure; may explode if heated.

Cylinder Identification: Gas Link Wales / Gas Link Group.

Valve Connection: BS 341 No. 8

Ensure all users of this product understand the hazards of asphyxiation.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

DISCLAIMER

Details given in this document are believed correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

For more information contact Gas Link Wales on 01443 222092